

ACRYLIC Facade Paint | A-100

Romolo acrylic paint, with the trade name A100, is a single-component product based on latex polymers and acrylic resins, as well as cellulose compounds, formulated using ionization technology. This product is for consumption and can be used for painting various interior and exterior surfaces. In addition to its technical superiority, it is also cost-effective and efficient in terms of execution speed.



Physical And Chemical Specs

Special Weight	1.4 gr/cm ³
Color	White
Physical Form	Liquid
PH	7-8
Average Particle Size	20 Micron
Density	1.4±0.1 gr/cm ³
Glossiness	Glossy
Viscosity	110 Ku
Drying Time	30 min
Mix Percentage With Water	10-20 %
Impermeability	100 %
Application Temp	5-40 C

Packaging | 10 | KG

Specifications :

- anti-moss and algae, and antibacterial
- Very high resistance to UV rays and CO₂
- Completely washable and with a low odor, nature-friendly
- Very high coverage power and non-allergenic
- Long-lasting against various water and moisture penetration
- Extraordinary resistance to extreme temperature and humidity changes
- Fast drying speed, easy application, dilutable with water
- Exceptional adhesion to old paint and most building materials

Applications:

- Suitable for painting various cement surfaces
- Suitable for painting various wooden surfaces
- Suitable for painting various concrete surfaces
- Suitable for painting various gypsum and cement panels
- Suitable for painting various interior and exterior surfaces
- Suitable for use in sculpture, pottery, and ceramic industries
- Suitable for painting various interior and exterior brick surfaces
- Suitable for painting various interior and exterior wooden surfaces

● How to use:

Romolo acrylic paint can be used as a surface paint for painting various interior and exterior surfaces. It can be used for painting facades in all buildings. First, make sure the surface is free of dust and dirt and completely dry. Then, dilute the desired paint with a clean and salt-free amount of water and apply it to the surfaces using a brush, a hairbrush, or a spray gun. If applying a new layer, it is possible after at least 3 hours of the initial painting. If the surface is uniform, one kilogram of Romolo acrylic paint is sufficient to cover 4-5 square meters.

Attention:

Before using, thoroughly mix the paint and then apply. Avoid using the paint table under direct sunlight. Use acrylic paint for color change. Strictly avoid using the paint table on all wet surfaces. The painted surface can be washed after 14 days.

● Packaging

Romolo Acrylic Primer is offered in **10 KG** packages.

● Storage

The recommended temperature range for storing the tile adhesive is between **10-30°C**. The product has a shelf life of 12 months when kept in its original, unopened packaging. It is important to store it away from direct sunlight, extreme cold, heat, and frost to maintain its quality and effectiveness.

● Safety

To ensure safety, it is advised to avoid direct contact with the eyes and skin. It is recommended to wear gloves and protective glasses when handling the product. In the event of accidental contact with the eyes, it is crucial to immediately rinse them with lukewarm water for a minimum of 15 minutes.

! The suitable working temperature is between 5 to 40 degrees Celsius, the drying time varies between 12 to 72 hours depending on the weather conditions.

ACRYLIC
FACADE PAINT



PLUS series | **A - 100**

CERTIFICATES

ISO 9001 : 2015

ISO 45001 : 2018

ISO 10002 : 2018

ISO 10668 : 2010

ISO 10004 : 2018

ISO 14001 : 2015

CE CERTIFICATE

IMS CERTIFICATE

HSE - MS CERTIFICATE



Construction adhesives
Construction Paints
Concrete Additives
Paint additives

Italian Processed
Construction
Materials