

## ACRYLIC Primer | **A-200**

Acrylic paint A-200, manufactured by Romolo, is a single-component product based on latex, acrylic resins, and cellulose compounds. This product is formulated using ionization technology. It is a consumable material and can be used for painting various interior and exterior surfaces. In addition to its technical superiority, it is also cost-effective and has a fast execution speed.



### Physical And Chemical Specs

Special Weight	1.5 gr/cm <sup>3</sup>
Color	White
Physical Form	Liquid
PH	7-8
Average Particle Size	30 Micron
Density	1.5±0.1 gr/cm <sup>3</sup>
Glossiness	Glossy
Viscosity	130 Ku
Drying Time	20 min
Mix Percentage With Water	5-20 %
Impermeability	100 %
Application Temp	5-40 C

**Packaging** | 10 | KG

### Specifications :

- Very high resistance to UV rays
- Very high coverage power and non-allergenic
- Anti-moss and anti-algae and anti-bacterial coating
- Low odor, nature-friendly and completely washable
- Fast drying speed, easy application, dilutable with water
- Exceptional adhesion to old paint and most building materials
- Long-lasting resistance against water penetration and various moisture levels
- Extraordinary resistance to temperature changes, abrasion, and moisture

### Applications:

- Suitable for painting various cement surfaces
- Suitable for painting various wooden surfaces
- Suitable for painting various concrete surfaces
- Suitable for painting various gypsum and cement panels
- Suitable for painting various interior and exterior surfaces
- Suitable for use in sculpture, pottery, and ceramic industries
- Suitable for painting various interior and exterior brick surfaces
- Suitable for painting various interior and exterior wooden surfaces

## How to use:

**Romolo acrylic primer** can be used as a primer for painting various interior and exterior surfaces. First, make sure the surface is free of dust and dirt and ensure it is completely dry. Then, dilute the desired paint with a clean and salt-free amount of water and apply it to the surfaces using a brush or spray gun. If necessary, a new layer can be applied after a minimum of 3 hours from the initial painting. If the surface is uniform, one kilogram of Romolo acrylic paint is sufficient to cover 4-5 square meters.

### Attention:

Before using, thoroughly mix the paint and then apply. Avoid using the paint table under direct sunlight. Use acrylic paint for color change. Strictly avoid using the paint table on all wet surfaces. The painted surface can be washed after 14 days.

## Packaging

Romolo Acrylic Primer is offered in **10 KG** packages.

## Storage

The recommended temperature range for storing the tile adhesive is between **10-30°C**. The product has a shelf life of 12 months when kept in its original, unopened packaging. It is important to store it away from direct sunlight, extreme cold, heat, and frost to maintain its quality and effectiveness.

## Safety

To ensure safety, it is advised to avoid direct contact with the eyes and skin. It is recommended to wear gloves and protective glasses when handling the product. In the event of accidental contact with the eyes, it is crucial to immediately rinse them with lukewarm water for a minimum of 15 minutes.

**!** The suitable working temperature is between 5 to 40 degrees Celsius, the drying time varies between 12 to 72 hours depending on the weather conditions.

**ACRYLIC**  
Primer



**PLUS** series | **A-200**

## CERTIFICATES

ISO 9001 : 2015  
ISO 45001 : 2018  
ISO 10002 : 2018  
ISO 10668 : 2010  
ISO 10004 : 2018  
ISO 14001 : 2015  
CE CERTIFICATE  
IMS CERTIFICATE  
HSE - MS CERTIFICATE



Construction adhesives  
Construction Paints  
Concrete Additives  
Paint additives

Italian Processed  
Construction  
Materials

