

SEMI-GLOSS Acrylic Paint | **A-240**

Romolo Semi-Gloss acrylic paint is single-component product based on Latex, acrylic resin and cellulosic formulated with ionizing technology. this product is ready to use for painting various indoor and outdoor surfaces. in addition of technical advantages, it is also less time consuming and financially beneficial



Physical And Chemical Specs

Special Weight	1.3 gr/cm ³
Color	White
Physical Form	Liquid
PH	7-8
Average Particle Size	30 Micron
Glossiness	Semi-Glossy
Density	1.3±0.1
Viscosity	110 Ku
Drying Time	20 min
Mix Percentage With Water	5-20 %
Impermeability	100 %
Application Temp	5-40 C

Packaging | 1 | 4 | 10 | KG

Specifications :

- Fully washable, less odor, nature-friendly
- High capability of covering and anti-allergic
- Highly resistant against UV radiation and CO₂
- Antifungal, anti-moss, anti-algae and anti-bacterial
- Quick drying, easy to use and dilutable with water
- High stable impermeability against water and humidity
- Resistant to temperature rise and drops, humidity and abrasion
- Excellent adhesion to old painted surfaces and building materials

Applications:

- Suitable for painting plaster surfaces
- Suitable for painting concrete surfaces
- Suitable for painting cement surfaces
- Suitable for painting indoor and outdoor surfaces
- Suitable for painting plaster and cement panels
- Suitable for painting all wooden indoor and outdoor surfaces
- Suitable for painting various brick surfaces indoors and outdoors
- Usable in sculpting industries, tile making and plaster tools.

● How to use:

Romolo semi-gloss acrylic paint is perfect for both interior and exterior surfaces. Simply prepare the surface by removing dust and ensuring it is dry, then dilute the paint with clean, salt-free water and apply with a brush, roller, or spray gun. A new layer can be applied after 3 hours.

One kilogram covers 5-4 square meters. The ideal working temperature is 40-50 C , and drying time ranges from 12 to 72 hours depending on weather conditions.

Attention:

Thoroughly stir the color before applying and avoid painting in direct sunlight. Use a base of acrylic colors to change the color, and avoid painting on wet surfaces. The painted surface can be washed after 14 days.

● Packaging

SEMI-GLOSS Acrylic Paint is offered in **1, 4 and 10 KG** packages for your ease of use and preference.

● Storage

The recommended temperature range for storing the tile adhesive is between **10-30°C**. The product has a shelf life of 12 months when kept in its original, unopened packaging. It is important to store it away from direct sunlight, extreme cold, heat, and frost to maintain its quality and effectiveness.

● Safety

To ensure safety, it is advised to avoid direct contact with the eyes and skin. It is recommended to wear gloves and protective glasses when handling the product. In the event of accidental contact with the eyes, it is crucial to immediately rinse them with lukewarm water for a minimum of 15 minutes.

! The suitable working temperature is between 5 to 40 degrees Celsius, the drying time varies between 12 to 72 hours depending on the weather conditions.

SEMI-GLOSS
Acrylic PAINT



PLUS series | **A+ 240**

CERTIFICATES

ISO 9001 : 2015

ISO 45001 : 2018

ISO 10002 : 2018

ISO 10668 : 2010

ISO 10004 : 2018

ISO 14001 : 2015

CE CERTIFICATE

IMS CERTIFICATE

HSE - MS CERTIFICATE



Construction adhesives
Construction Paints
Concrete Additives
Paint additives

Italian Processed
Construction
Materials