

PLASTIC Emulsion Paint | **P-200**

Semi-Plastic Paint Romolo with the trade name P100 is a single-component product based on latex, acrylic resins, and cellulose compounds. This product is a consumable material and can be used for painting various interior surfaces. In addition to its technical superiority, it is also cost-effective and has a fast execution speed.



Physical And Chemical Specs

Special Weight	1.4 gr/cm ³
Color	White
Physical Form	Liquid
PH	7-8
Average Particle Size	30 Micron
Density	1.4±0.1 gr/cm ³
Glossiness	Matte
Viscosity	120 Ku
Drying Time	20 min
Mix Percentage With Water	5-30 %
Impermeability	50 %
Application Temp	5-40 C

Packaging | 1 | 5 | 12 | KG

Specifications :

- Anti-fouling, anti-algae, and anti-bacterial
- High resistance to UV rays
- Odorless, environmentally friendly
- Anti-mold, non-toxic, suitable for utensils
- Very high coverage power, non-allergenic
- Relative resistance to temperature changes, wear, and moisture
- Fast drying, easy to apply, can be diluted with water
- Excellent adhesion to old paint and most building materials

Applications:

- Suitable for painting various wooden surfaces
- Suitable for painting various concrete surfaces
- Suitable for painting various cement surfaces
- Suitable for painting various interior and ceiling surfaces
- Suitable for painting various gypsum and cement panels
- Suitable for painting various wooden and stone surfaces
- Suitable for use in sculpture, pottery, design, and calligraphy industries

How to use:

The Romolo semi-plastic color can be used as a surface color and a base color for painting various interior surfaces and ceilings (horizontal and vertical). First, make sure the desired surface is free of dust and dirt and completely dry. Then, dilute the desired color with a clean and salt-free amount of water and paint the surfaces using a brush or spray gun. If applying a new layer, it is possible after at least 3 hours of the initial painting. If the surface is uniform, one kilogram of Romolo semi-gloss acrylic paint is sufficient to cover 5-4 square meters.

Attention:

Before using, thoroughly mix the paint and then apply. Avoid using the paint table under direct sunlight. Use acrylic paint for color change. Strictly avoid using the paint table on all wet surfaces. The painted surface can be washed after 14 days.

Packaging

Romolo Plastic Paint is offered in **1, 5 and 12 KG** packages.

Storage

The recommended temperature range for storing the tile adhesive is between **10-30°C**. The product has a shelf life of 12 months when kept in its original, unopened packaging. It is important to store it away from direct sunlight, extreme cold, heat, and frost to maintain its quality and effectiveness.

Safety

To ensure safety, it is advised to avoid direct contact with the eyes and skin. It is recommended to wear gloves and protective glasses when handling the product. In the event of accidental contact with the eyes, it is crucial to immediately rinse them with lukewarm water for a minimum of 15 minutes.

! The suitable working temperature is between 5 to 40 degrees Celsius, the drying time varies between 12 to 72 hours depending on the weather conditions.



National Standard 289

PLUS SERIES | **P-200**

CERTIFICATES

ISO 9001 : 2015
ISO 45001 : 2018
ISO 10002 : 2018
ISO 10668 : 2010
ISO 10004 : 2018
ISO 14001 : 2015
CE CERTIFICATE
IMS CERTIFICATE
HSE - MS CERTIFICATE



Standard Certificate
6 6 9 6 3 7 4 0 2 4



Construction adhesives
Construction Paints
Concrete Additives
Paint additives

Italian Processed
Construction
Materials