

A-Plus Paints



Includes:

A complete set for painting all kinds of industrial and semi-industrial building projects

A240

A220

A100

A200

✓ Anti-bacterial

✓ Powerful Coverage

✓ Odorless

Introduction:

Romolo acrylic paints (glossy, semi-glossy, matte, priming, and facade) are single-component, water-based products. These products are characterized by high coverage power, fast drying speed, resistance to water penetration and various moisture types, low odor, and non-sensitivity. They are ready-to-use and suitable for painting various interior and exterior surfaces.



رنگ آکرلیک نما

A100

Density: 1.4 ± 0.1 gr/cm³

Glossiness: Matte

Viscosity: 110 Ku

PH: 7-8

Mixture with water 5-20%



رنگ آکرلیک آستری

A200

Density: 1.5 ± 0.1 gr/cm³

Glossiness: Matte

Viscosity: 130 Ku

PH: 7-8

Mixture with water 5-20%



رنگ آکرلیک مات

A220

Density: 1.3 ± 0.1 gr/cm³

Glossiness: Matte

Viscosity: 110 Ku

PH: 7-8

Mixture with water 5-20%



رنگ آکرلیک نیم برلق

A240

Density: 1.3 ± 0.1 gr/cm³

Glossiness: Semi-glossy

Viscosity: 110 Ku

PH: 7-8

Mixture with water 5-20%

Specifications:

Anti-fungal, anti-moss, anti-algae and antibacterial.
High covering power and non-allergic, no smell.
Completely washable, resistant to water and humidity penetration.
High drying speed, ease of application, can be diluted with water.

Applications:

Suitable for painting all types of plaster surfaces, concrete surfaces, cement surfaces, wooden surfaces, brick surfaces, all types of plaster and cement panels, in all indoor and outdoor spaces, can be used in sculpture, pottery, and plaster tools industries.

ROMOLO

www.romolo.ir | romolo.official



A-Plus Paints

Storage

The suitable temperature for storing the product is 10-30 degrees Celsius, the useful life of this product is one year provided that it is kept in a covered environment and away from moisture, freezing, extreme heat and direct sunlight.

Safety Cautions

Avoid direct contact with eyes and skin. Use gloves, glasses and appropriate clothing during application. In case of possible contact with eyes, wash immediately with lukewarm water for 15 minutes.

Packages

Romolo paste tile adhesive in packages of 1, 5 and 12.5 kg
It is produced and supplied.

Where to buy our products?

To buy this product, please visit: romolo.ir or our instagram page: [romolo.official](https://www.instagram.com/romolo.official). you can also visit Romolo showroom located in: Ava-General complex building, Shad-Abad, Tehran, Iran.

How to Use

You can use various types of Romulo acrylic paints (glossy, semi-gloss, matte, primer, and decorative) as topcoats for painting different interior and exterior surfaces.

First, ensure the surface is free from dust and completely dry. Then, dilute the desired paint with a small amount of clean, salt-free water. Apply the paint using a roller, brush, or spray gun.

If applying an additional coat, wait at least 3 hours after the initial painting. For uniform surfaces, 1 kilogram of Romulo acrylic paint is sufficient to cover 4 to 5 square meters in one coat.

Important Notes:

Thoroughly stir the paint before use.

Avoid painting under direct sunlight.

Use acrylic colorants to modify the color.

Strictly avoid painting on any damp surfaces.

The painted surface can be washed after 14 days.

Attention

The suitable working temperature is between 5 to 40 degrees Celsius, the drying time varies between 12 to 72 hours depending on the weather conditions.