

Silicone Paint & Insulant A140



Paint & Waterproofing

- 1 Kg
- 10 Kg

- High facades
- Tanks and Pools
- Facades
- Various Surfaces

Introduction:

Romolo Silicon paint, with the trade name A140, is a single-component product based on latex polymers and acrylic resins, as well as cellulose compounds, formulated by ionization technology. This product is for consumption and can be used for painting various interior and exterior surfaces. In addition to its technical superiority, it is also cost-effective and efficient in terms of execution speed.

Specifications

Special Weight	1.36 gr/cm ³
Color	Blue ● Black ● White ○
Physical Form	Liquid
PH	7-8
Average Particle Size	20 micron
Glossiness	Semi-Glossy
Density	1.36 ±0.1 gr/cm ³
Viscosity	120 Ku
Drying Time	20 Min
Mixing Percentage with water	5-20%
Impermeability	100%
Application Temp	5-40 C°

Specifications:

- anti-moss and algae, and antibacterial
- high resistance to UV rays and CO
- Completely washable and with a low odor, nature-friendly
- Very high coverage power and non-allergenic
- Long-lasting against various water and moisture penetration
- Extraordinary resistance to extreme temperature and humidity changes
- Fast drying speed, easy application, dilutable with water
- Exceptional adhesion to old paint and most building materials

Applications:

- Suitable for painting various cement surfaces
- Suitable for painting various concrete surfaces
- Suitable for painting various gypsum and cement panels
- Suitable for painting various interior and exterior surfaces
- Suitable for use in sculpture, pottery, and ceramic industries
- Suitable for painting various interior and exterior brick surfaces
- Suitable for painting various interior and exterior wooden surfaces

ROMOLO

www.romolo.ir | romolo.official



Silicone Paint & Insulant

A140

ROMOLO NEW GENERATION OF MATERIALS

Storage

The appropriate temperature for keeping the product is 10-30 degrees Celsius, the useful life of this product is 24 months provided that it is kept in a covered environment and away from moisture, freezing, extreme heat and direct sunlight.

Safety Cautions

Avoid direct contact with eyes and skin. Use gloves, glasses and appropriate clothing during application. In case of possible eye contact, wash immediately with lukewarm water for 15 minutes.

Packages

Romolo silicone paint with the brand name A-140 is available in 10. and 1 KG buckets.

Attention

The suitable temperature for usage is 5 to 40 degrees Celsius. The drying time of the product varies from 12 to 72 hours depending on the weather conditions.

How to use:

Romolo acrylic paint can be used as a surface paint for painting various interior and exterior surfaces. It can be used for painting facades in all buildings. First, make sure the surface is free of dust and dirt and completely dry. Then, dilute the desired paint with a clean and salt-free amount of water and apply it to the surfaces using a brush, a hairbrush, or a spray gun. If applying a new layer, it is possible after at least 3 hours of the initial painting. If the surface is uniform, one kilogram of Romolo acrylic paint is sufficient to cover 6-8 square meters.

Attention:

Before using, thoroughly mix the paint and then apply. Avoid using the paint table under direct sunlight. Use acrylic paint for color change. Strictly avoid using the paint table on all wet surfaces. The painted surface can be washed after 14 days.

Colors:

Available colors:

Blue

Black

White

Where to buy our products?

To buy this product, please visit: romolo.ir or our instagram page: [romolo.official](https://www.instagram.com/romolo.official). you can also visit Romolo showroom located in: Ava-General complex building, Shad-Abad, Tehran, Iran.

ROMOLO

www.romolo.ir | [@romolo.official](https://www.instagram.com/romolo.official)

☎ 021-650 20 675

☎ 021-650 20 642

☎ 021-650 20 684

☎ 021-650 20 658