Tile Adhesive **Powders**

Poweful Adhesion

■ 20 Kg





Water Resistant

Dead Load Reduction

Indtroduction:

Romolo Multi Plus Tile Adhesive Powders are mineral-based products that offer strong adhesion and ease of use for installation on various surfaces, they are designed with waterproof compounds and ionization technology, making it suitable for applications like pools, water tanks, saunas, jacuzzis, and elevated slab stone installations. This adhesive powder reduces the dead load of the building and can be used on different types of surfaces.



ADHESIVE

- Suitable for various tiles and mosaics
- Suitable only for floor installing



AP-6 **SLAB AND TILE ADHESIVE**

- Suitable for porcelain tiles
- Applicable in high heights
- Suitable for floor and wall



AP-8 **ADHESIVE**

- Suitable for various slabs, and slabs in pools or jaquzis
- Applicable in high heights
- Suitable for floor and vertical installing



AP_10 SLAB/BLOCK **ADHESIVE**

- Suitable for installing stones on facades, pool slabs,
- Environmental stones and statues
- Applicable in high heights suitable for floor and wall



















Tile Adhesive Powders AP

Storage

The recommended temperature range for storing the product is between 10-30°C. The product has a shelf life of 12 months when kept in its original, unopened packaging. It is important to store it away from direct sunlight, extreme cold, heat, and frost to maintain its quality and effectiveness.

Safety Cautions

Avoid direct contact with eyes and skin. Use gloves, glasses and appropriate clothing during application. In case of possible contact with eyes, wash immediately with lukewarm water for 15 minutes.

Packages

Romolo Multi Plus Tile Adhesive Powders are offered in **20KG** packages for your ease of use and preference.

Attention

The suitable temperature for usage is 5 to 40 degrees Celsius. The drying time of the product varies from 12 to 72 hours depending on the weather conditions.

How to use

To summarize, before applying the Romolo Multi Plus Tile Adhesive Powders, it is important to clean the surface and create a scratch for better adhesion. The recommended ratio is 4 kg of glue mixed with 1 liter of water. Thoroughly mix the adhesive before applying it behind the tile and at the desired level. The consumption rate is generally 4-5 kg per square meter.

Attention:

The suitable temperature range for using the adhesive is 5-40°C. This adhesive has high adhesion due to its low water absorption and should be used within 7-10 minutes after mixing with water.

Specifications

- · Fast adhesion and drying
- . Low cost and easy installation
- Suitable for use in all climates
- Capaballity of use in high altitudes
- Strong adhesion to all building materialsHigh resistance to moisture, steam, acid, and petroleum
- Superior flexibility preventing cracks or detachment of tiles or stones
- Rapid drying and efficient rigidity, enabling fast preparation and performance

Where to buy our products?

To buy this product, please visit: romolo.ir or our instagram page: romolo.official. you can also visit Romolo showroom located in: Ava-General complex building, Shad-Abad, Tehran, Iran.

