

Easy Grout Powder H10



Ready and Easy to Use  300 gr

Anti-Bacterial

Acid Resistant

Water Proof

Introduction:

H10 is the trade name for Romolo ionized powder and cement-based micronized mineral powders. The shell powder is a chemical additive and binder compound formulated with ionization technology. The special feature of this product is its extremely strong adhesion to various construction materials and versatile application. It is suitable for plastering and grouting various surfaces in both indoor and outdoor spaces.

Specifications

Special Weight	3.5 gr/cm ³
Color	White
Physical Form	Powder
PH	7-8
Average Particle Size	800 mesh
Application Temp	5-40° C
Density	3.5 gr/cm ³
Shear Adhesion Strength	0.8 < M pa
Adhesion Time	Minutes 20
Drying Time	Minutes 60
Water Mixing Percentage	25-30%
Impermeability	95%

Application:

- Suitable for grouting and sealing various types of tiles, ceramics, mosaics, brick facades, chimney facades, decorative tiles, stone facades, pool and sauna area tiles. Foam plastic for decorative glass, stone, synthetic, and waterproofing of washing joints. Jacuzzi and toilet in all indoor and outdoor spaces.

ROMOLO

www.romolo.ir | [@romolo.official](https://www.instagram.com/romolo.official)



Easy Grout Powder H10

Storage

The suitable temperature for storing the product is 10-30 degrees Celsius, the useful life of this product is one year provided that it is kept in a covered environment and away from moisture, freezing, .extreme heat and direct sunlight

Safety Cautions

Avoid direct contact with eyes and skin. Use gloves, glasses and appropriate clothing during application. In case of possible contact with eyes, wash immediately with lukewarm water for 15 minutes.

Packages

Romolo's white porcelain powder adhesive is produced and supplied in 20 kg packages.

Attention

The suitable temperature for usage is 5 to 40 degrees Celsius. The drying time of the product varies from 12 to 72 hours depending on the weather conditions.

How to Use

Clean and completely dry the area of use. Then open the bottle cap and pour warm water to the top. After one minute, close the bottle cap and shake well to mix the contents. The resulting mixture is the material to be used. Clean and completely dry the area of use. Then open the bottle cap and pour warm water to the top. After one minute, close the bottle cap and shake well to mix the contents. The resulting mixture is the material to be used.

Specifications

- Quick drying and fast adhesion
- Suitable for thin and thick layers
- Speed in material preparation and execution
- Ability to be executed vertically and horizontally
- Exceptional adhesion to various building materials
- Suitable for various climates and weather conditions
- Waterproof, acid-resistant, salt-resistant, and antibacterial
- High permeability for filling gaps and voids during execution

Where to buy our products?

To buy this product, please visit: romolo.ir or our instagram page: [romolo.official](https://www.instagram.com/romolo.official). you can also visit Romolo showroom located in: Ava-General complex building, Shad-Abad, Tehran, Iran.