

Plastic and Semi-Plastic Paints

P100

P200



Tagline Here

1Kg 5Kg 12 Kg

- ✓ Anti-Bacterial
- ✓ Odorless
- ✓ Exceptional Coverage

Introduction:

Romolo plastic and semi-plastic paints are single-component products based on latex, acrylic resins and cellulose compounds, which are formulated with ionization technology. This product is ready-to-use and can be used for painting all kinds of interior surfaces, which, in addition to its technical advantages, is also cost-effective in terms of economy and execution speed.

Specifications

● Special Weight (P100)	1.5 ± 0.1 gr/cm ³
● Special Weight (P200)	1.4 ± 0.1 gr/cm ³
Glossiness	Matt
Color	White
Physical Form	Liquid
PH	7-8
Average Particle Size	30 Micron
Application Temp	5-40° C
Density	1.5±0.1 gr/cm ³
Viscosity	120 Ku
Adhesion Time	Minutes 20
Drying Time	Minutes 20
Mixing Percentage With Water	5-20%
● Impermeability (P100)	50%
● Impermeability (P200)	100%

Specifications:

Anti-moss, anti-algae and antibacterial
High resistance to UV rays and CO₂
Odorless, nature and environment friendly
Anti-mold, non-toxicity, suitable pen
Very high coverage and no sensitivity
Relative resistance to temperature changes, wear and humidity
High drying speed, ease of application, can be diluted with water
Excellent adhesion to old paint and most building materials

Applications:

Suitable for painting all types of plaster surfaces
Suitable for painting all kinds of concrete surfaces
Suitable for painting all types of cement surfaces
Suitable for painting all types of interior surfaces and ceilings
Suitable for painting all types of plaster and cement panels
Suitable for painting all kinds of wooden surfaces and brick surfaces
Can be used in sculpture, pottery, design and calligraphy industries

ROMOLO

www.romolo.ir | romolo.official



P100 Plastic and P200 Semi-Plastic Paints

Storage

The suitable temperature for storing the product is 10-30 degrees Celsius, the useful life of this product is one year provided that it is kept in a covered environment and away from moisture, freezing, .extreme heat and direct sunlight

Safety Cautions

Avoid direct contact with eyes and skin. Use gloves, glasses and appropriate clothing during application. In case of possible contact with eyes, wash immediately with lukewarm water for 15 minutes.

Packages

Romolo paste tile adhesive in packages of 1, 5 and 12.5 kg
It is produced and supplied.

Where to buy our products?

To buy this product, please visit: romolo.ir or our instagram page: [romolo.official](https://www.instagram.com/romolo.official). you can also visit Romolo showroom located in: Ava-General complex building, Shad-Abad, Tehran, Iran.

How to Use

Romulo's plastic and semi-plastic colors, which are part of the category of plastic colors, can be used as top and lining colors for painting all kinds of interior and ceiling surfaces (horizontal and vertical). First, make the desired surface free of dust and make sure it is completely dry, then dilute the desired color with some clean, salt-free water and paint the surface using a brush roller or gun. do it

In case of applying a new layer, it is possible after at least 3 hours of the initial painting. If the work surface is uniform, one kilogram of Romulo semi-gloss acrylic paint is enough to cover 4-5 square meters.

Note:

Stir the color completely before use and then apply. Avoid painting under direct sunlight. Use the mother of acrylic colors to color together. Avoid painting on all wet surfaces. The painted surface can be washed after 14 days.

Attention

The suitable working temperature is between 5 to 40 degrees Celsius, the drying time varies between 12 to 72 hours depending on the weather conditions.