

Ready Putty RP4



Ready and easy to use  1.5 Kg

Odorless

Economic

Exceptional Adhesion

Introduction:

It can be said that RP4 is a versatile material. It is a unique product based on latex and micronized mineral powders and shell powder, formulated using ionization technology. The special features of this product include its exceptional adhesion to various surfaces and its wide range of applications. In addition to its technical superiority, the use of this product is cost-effective due to its greater surface coverage and reduced paint consumption during application.

Specifications

Special Weight	1.7 gr/cm ³
Color	White
Physical Form	Pasty
PH	7-8
Average Particle Size	30 micron
Application Temp	5-40° C
Density	1.7 gr/cm ³
Viscosity	High VIS
Adhesion Time	Minutes 10
Drying Time	Minute 1
Water Mixing Percentage	30-40%
Impermeability	0%

Specifications:

- Reduced paint consumption during application
- Exceptional resistance to pressure, heat, and moisture
- High adhesion and impermeability in deep thicknesses
- Less softening and sanding required, no need for re-staining
- Fast initial drying without causing allergy or having any odor
- Compatibility with various plastic, acrylic, and oil-based paints

Applications:

- Suitable for sealing various gypsum and cement surfaces.
- Suitable for painting various interior and exterior surfaces.
- Compatible with any type of oil-based, plastic, and acrylic paint.
- Suitable for use in sculpture, ceramics, and gypsum tools industry.
- Suitable for painting and sealing metal, wood, and gypsum panels.

ROMOLO

www.romolo.ir | [@romolo.official](https://www.instagram.com/romolo.official)



Ready Putty RP4

Storage

The suitable temperature for storing the product is 10-30 degrees Celsius, the useful life of this product is one year provided that it is kept in a covered environment and away from moisture, freezing, extreme heat and direct sunlight

Safety Cautions

Avoid direct contact with eyes and skin. Use gloves, glasses and appropriate clothing during application. In case of possible contact with eyes, wash immediately with lukewarm water for 15 minutes.

Packages

Romolo ionized ready-to-use putty is supplied in a 1.5 kg container.

How to Use

Clean and completely dry the desired surfaces from any contamination. Then, smooth the desired surface with a scraper and inspect it until it is completely dry. The amount of product consumption varies depending on the depth and material of the surface being used.

In concrete surfaces, clean the surface before smoothing and apply oil to it. For deep cracks, perform the smoothing process twice with a minimum interval of four hours. In metal surfaces, clean the metal surface before smoothing and apply suitable paint.

Attention

The suitable temperature for usage is 5 to 40 degrees Celsius. The drying time of the product varies from 12 to 72 hours depending on the weather conditions.

Where to buy our products?

To buy this product, please visit: romolo.ir or our instagram page: [romolo.official](https://www.instagram.com/romolo.official). you can also visit Romolo showroom located in: Ava-General complex building, Shad-Abad, Tehran, Iran.